

A different sleep apnea classification system with neural network based on the acceleration signals

Ahmet Hayrettin Yüzer^a, Harun Sümbül^b, Majid Nour^c, Kemal Polat^{d,*}

^a Department of Electrical and Electronics Engineering, Karabuk University, Karabuk, Turkey

^b Yesilyurt D.C. Vocational School, Ondokuz Mayıs University, Samsun, Turkey

^c Department of Electrical and Computer Engineering, Faculty of Engineering, King Abdulaziz University, Jeddah 21589, Saudi Arabia

^d Department of Electrical and Electronics Engineering, Faculty of Engineering, Bolu Abant İzzet Baysal University, 14280 Bolu, Turkey

ARTICLE INFO

Article history:

Received 29 December 2019

Received in revised form 12 January 2020

Accepted 18 January 2020

Available online 25 January 2020

Keywords:

Sleep apnea

Acceleration sensor

Acceleration data

Artificial neural network

Medical decision making

ABSTRACT

Background and objective: The apnea syndrome is characterized by an abnormal breath pause or reduction in the airflow during sleep. It is reported in the literature that it affects 2% of middle-aged women and 4% of middle-aged men, approximately. This study has vital importance, especially for the elderly, the disabled, and pediatric sleep apnea patients.

Methods: In this study, a new diagnostic method is developed to detect the apnea event by using a micro-electromechanical system (MEMS) based acceleration sensor. It records the value of acceleration by measuring the movements of the diaphragm in three axes during the respiratory. The measurements are carried out simultaneously, a medical spirometer (Fukuda Sangyo), to test the validity of measurement results. An artificial neural network model was designed to determine the apnea event. For the number of neurons in the hidden layer, 1–3–5–10–18–20–25 values were tried, and the network with three hidden neurons giving the most suitable result was selected. In the designed ANN, three layers were formed that three neurons in the hidden layer, the two neurons at the input, and two neurons at the output layer.

Results: A study group was formed of 5 patients (having different characteristics (age, height, and body weight)). The patients in the study group have sleep apnea (SA) in different grades. Several 12.723 acceleration data (ACC) in the XYZ-axis from 5 different patients are recorded for apnea event training and detection. The measured accelerometer (ACC) data from one of the patients (called H1) are used to train an ANN. During the training phase, MSE is used to calculate the fitness value of the apnea event. Then Apnea event is detected successfully for the other patients by using ANN trained only with H1's ACC data. **Conclusions:** The sleep apnea event detection system is presented by using ANN from directly acceleration values. Measurements are performed by the MEMS-based accelerometer and Industrial Spirometer simultaneously. A total of 12723 acceleration data is measured from 5 different patients. The best result in 7000 iterations was reached (the number of iterations was tried up to 10,000 with 1000 steps). 605 data of only H1 measurements are used to train ANN, and then all data used to check the performance of the ANN as well as H2, H3, H4, and H5 measurement results. MSE performance benchmark shows us that trained ANN successfully detects apnea events. One of the contributions of this study to literature is that only ACC data are used in the ANN training step. After training for one patient, the ANN system can monitor the apnea event situation on-line for others.

© 2020 Elsevier Ltd. All rights reserved.

1. Introduction

The breathing provided by contraction of the diaphragm muscle layer that separates the abdominal and chest cavity is an indis-

pensable involuntary movement for living creatures. During the inspiration and expiration, the diaphragm size differs. Changes in the diaphragm size can give a clue to many diseases (the diaphragm eventration, chronic obstructive pulmonary disease (COPD), sleep apnea (SA), etc.) [1,2].

Stopping the airflow for at least 10 s during breathing is defined as Sleep Apnea. An apnea event is a reduction in the magnitude of respiration movement to less than 5% of normal value in breathing cases for a certain amount of time [3]. It can cause congestion of

* Corresponding author.

E-mail addresses: hayrettinyuzer@karabuk.edu.tr (A.H. Yüzer), harun.sumbul@omu.edu.tr (H. Sümbül), mnour@kau.edu.sa (M. Nour), kpolar@ibu.edu.tr (K. Polat).

the throat's airway, which reduced the inhaled amount of oxygen during respiration [4]. Airflow congestion in each period of respiration is called apnea event [5]. Although the occurrence of apnea events might be physiological, if more than 5 events of apnea occur per sleeping hour, they would usually be regarded as being pathological [6]. The apnea syndrome is characterized by abnormal breath pause or reduction during sleep. It is reported in the literature that it affects 2% of middle-aged women and 4% of middle-aged men, approximately [7].

There are three types of SA, central sleep apnea (CSA), obstructive sleep apnea (OSA), and mixed sleep apnea (MSA). The diaphragm muscles are excited by the human brain to take a breath during sleep. CSA can be defined as a short-term respiratory stop resulting from the absence of a signal from the brain. Similarly, OSA can be defined as a short-term respiratory stop despite muscle effort to take a breath existence of the brain to send a signal. Respiration is failed because of airway congestion. MSA is a combination of the previous two types of apnea [8].

According to the American Academy of Sleep Medicine (AASM) apnea scoring guide, two criteria are adequately considered to assess SA [9].

1. At least 90% reduction in airflow amplitude
2. This reduction should last for at least 10 s

So, it is necessary to know the airflow for apnea detection. Fig. 1 shows breathing effort in the abdominal region, depending on the airflow.

While the abdominal movements continue in the OSA and MSA at the time of apnea event, in CSA, abdominal movements are significantly reduced at the time of apnea. So, CSA information can be obtained through the breathing effort on the diaphragm. CSA is detected in this study.

In recent years, very different techniques have been developed that relate to the diagnostic work of the apnea event. Especially Artificial intelligence (AI) methods have been studied in many numbers of papers. Artificial Neural Networks (ANNs) method is one of the AI methods and is widely used in the apnea classification [11,12]. Besides, at the related works in the literature [13,14], Particle Swarm Optimization (PSO) and Machine Learning (ML) techniques are used to find a solution to diagnose apnea. Similarly, the detection of sleep apnea events from photoplethysmography (PPG) waves variation patterns during sleep was one of the most recent methods in recent times [15]. Apnea event detection using

the heart rate variability and the electrocardiogram-derived respiration signals [16], signal classification technique [17] and using a 3D camera are also different methods in literature [18]. The apnea events detection with the help of airflow signals [19] and respiratory signals [20] are also quite conventional methods.

The data about apnea events can also be measured by a spirometer with a suitable nozzle [21], although the spirometer is used to scan people who are at risk of pulmonary disease [22].

The accelerometer sensors measure the acceleration along the three axes (X, Y, and Z). It is possible to use the three axes measurement to determine the movement of the diaphragm during respiration [23]. The accelerometer sensors might be used as a reliable diagnostic technique for certain pulmonary diseases such as COPD, pulmonary hypertension, etc.

Since apnea is known to be a respiratory disease, so, many works have been done on the detection of apnea by using breathing signals. Many of these have occurred in the form of breath signal analysis through diaphragm movements [24–26]. Relation of accelerometer signals (ACC) and respiratory information have also been published in many studies [27,28].

This work aimed at the detection of apnea events using an accelerometer-based ANN model. For this purpose, diaphragm movements are monitored continuously with MEMS (microelectromechanical systems) based accelerometer, which placed on the patient's diaphragm. During sleep time, the apnea events are screened continuously by a closed-loop control system in real-time. If there is no movement on the diaphragm for at least 10 s, that means there is no acceleration on the sensor, this is detected by the accelerometer. The measurements are carried out simultaneously a medical spirometer (device (Fukuda Sangyo brand spirometry ST-75 model, Prg ver: 2.36B 16-Bit)) to test the validity of measurement. Continuous positive airway pressure mask used in patients for spirometer measurements.

2. Materials and methods

2.1. ACC measurement setup

Types of MEMS-based accelerometers using from military to health industry have been summarized in [29]. ADXL345, one of the MEMS-based 3-axis accelerometer with digital output, is used in the measurement setup. Details about the structure and properties of ADXL345 are given in [30] to detect the lying position. ACCs can use to diagnose a respiratory-related disease like apnea. In this




Fig. 1. Classification of apnea according to breathing signals, (a) airflow, (b) abdominal movement [10].

study, ACC data were measured with the developed measuring device (contains ADXL345 MEMS-based 3-axis accelerometer), defined in [31].




Fig. 2. The working principle of the system.

It was understood from the literature [32–35] that the ideal location for the accelerometer is the space between the 7th ribs, the region above the diaphragm (the solar plexus). Thus, in the designed system, the acceleration sensor was placed on a patient's diaphragm, to XY-plane become parallel to the floor and the z-axis perpendicular to the diaphragm. Placing the sensor on the patient's diaphragm and working principle of the system can be seen in Fig. 2. The sensor was connected to the body (the abdomen region) with the help of a belt.

Especially for patients with sleep apnea, the patient's position of residence is of great importance. The risk of sleep apnea increases with the position of the bed. Apnea/Hypopnea Index (AHI) is usually increased in the lying position on the back, while this rate decreases in the right or left side. When there is a half-decline in the AHI rate during sleep in other positions, positional Apnea is mentioned. Patients with positional sleep apnea were found to be lying in the supine position, in general [36]. This is a great risk for patients, and these patients need special therapy. Thus, in this study, apnea events in the supine position were detected.

Movements of the diaphragm may be in an arbitrary direction, so a three-axis acceleration sensor is used in the measurement setup – power axis of the gravitational acceleration (g) measured in real-time with an accelerometer [37]. During inspiration, the




Fig. 3. ANN structure with ACC input.




Fig. 4. ANN architecture.

diaphragm contracts and the lungs are filled with air. During this process, the thorax moves in both the ventral and cranial direction. Acceleration sensor values can be taken from either diaphragm or thorax.

The average lower and upper threshold values were determined for the measured acceleration values. (LTV: Lower threshold value; 0.32 g; UTV: upper threshold value: 0.42 g). Thus, the areas above and below the threshold values were regarded as normal breathing, while the areas in between above and below the threshold values were regarded as apnea. In the case of tiny movements, a threshold was taken, that means, the patient cannot get breathing and apnea starts.

All data were recorded on the SD card. The data were digitized at 20 Hz sampling frequency using 32-bit resolution. Each 32-bits of received float type data contained x, y, and z data. The transferred data size, $20 \times 3 \times 32 = 1920$ bits/sec, was suitable for a wireless transmission. 10 point averaging low pass filter was created to reduce the noise at the MATLAB program (version 7.12.0.635 (R2011a) 32-bit win32). DC components were thrown from the raw signal. In order to get rid of the high-frequency noise component of the obtained signals, a digital filter was designed in MATLAB. The filter used is 10 point moving average low-pass filtering, and smoothing algorithm (Smooth Algorithm) as shown in (1):

$$y[i] = \frac{1}{P} \sum_{j=0}^{P-1} x[i+j] \quad (1)$$

where x is a raw signal, y is averaged signal, P is the average number of points.

In this work, a total of 12.723 XYZ data measured with the help of the measurement system in the reference [30] was used in the designed ANN for apnea event detection.

The magnitude of the data set (total 12.723 measured data) was normalized in the range from 0 to 1 using Eq. (2):

$$S_i^{norm} = \frac{S_i - S_{min}}{S_{max} - S_{min}} \quad (2)$$

where S_i is the value of the i th ($i = 1, 2, \dots, 12723$) segment to be normalized and S_{max} and S_{min} are the biggest and the smallest values of the data set.

2.2. ANN structure with ACC input

In modeling with ANN, V7.12.0.635 (R2011a) Matlab software version which has Neural Network Toolbox is used. Acceleration values of the XYZ axes measuring by the developed device (ACC) were applied to the ANN as input after normalization. ANN structure with ACC input showed in Fig. 3.

2.3. ANN learned by backpropagation

ANN is a machine learning method that has become popular in recent times and is preferred in many areas [38,39]. The backpropagation (BP) algorithm is usually used to train multilayer ANNs [40,41]. Multilayer backpropagation networks are composed of three layers; input, hidden, and output layers. BP algorithms are supervised learning procedure to get optimum weights and biases between the input layer and the output layer.

In this study, the ANN system that has 3 inputs (XYZ) and one output (A- Apnea event) constructed shown in Fig. 4.

where,

i, j, and k are the input, hidden and output layers, respectively.

b_1, b_k ; biases,

w_1, w_2 ; weights,

A; apnea event,

The input layer has D neurons and input vector $I = [I_1, I_2, \dots, I_D]$, and the output layer has F neurons and has output vector $O = [O_1, O_2, \dots, O_F]$ while the hidden layer has E neurons. The output signals of the network (A) were compared with the desired output value (the target), which was found in the training data set. Weights and bias are the parameters that define the behavior. Input vector was constructed from ACC data (X, Y, and Z), and the output vector was constructed from A.

As the ANN algorithm, feed-forward neural networks named standard backpropagation training algorithm was preferred. In the designed ANN, three layers were formed that 3 neurons in the hidden layer, the 2 neurons at the input and 2 neurons at the output layer. In the hidden layer, 1-5-10-18-20-25 numbers of neurons were tried, and the network with 3 hidden neurons giving the most suitable result was selected. The best result in 7000 iterations was reached (the number of iterations was tried from 1 to




Fig. 5. Performance of ANN for H1.

10.000 with 1000 steps). The sigmoid (log-sig) function limiting the output in the range from 0 to 1 is one of the most commonly used activation function. Therefore, the log-sig function was selected as the activation function. The mathematical expression of this function was given in (3) and (4), [42].

$$netj = \sum_i w_{ij} I_i + b_j \quad (3)$$

$$fj = \frac{1}{1 + e^{-netj}} \quad (4)$$

where,
 $netj$ is the sum of the total weighted input and the bias,
 w_{ij} is the weight which is related to the connection between the node in the i th input layer and the node in the j th hidden layer,
 I_i is the input at the node in the i th input layer,
 b_j is the bias associated at each connection link between the input layer i and hidden layer j ,
 fj is the output of activation function at hidden layer j .

As an error function Mean Square Error (MSE) was used (Eq.5) in order to check the error at each iteration. The training process was stopped when the calculated MSE error is smaller than the predefined acceptable error [42].

$$MSE = \frac{1}{2} \sum_k (t_k - f_k)^2 \quad (5)$$

where,

Table 1
 Calculated MSE value of ANN for the patient H2, H3, H4 and H5 (ANN is trained by using only H1 data).

Patient No.	MSE
H1	0,0025316
H2	0,0025366
H3	0,0025364
H4	0,0025367
H5	0,0025368




Fig. 6. Apnea event detection performance of ANN with Spirometer measurement and accelerometer g values for the patient (a) H2, (b) H3, (c) H4, (d) H5.




Fig. 6 (continued)

k is the output layer,
 tk is the desired output at the kth output layer,
 fk is the final output at the kth output layer.

3. Experimental studies and results

Measurements were taken on 5 patients (H1: 2763, H2: 2748, H3: 2439, H4: 2436, H5: 2337) that were known to have apnea syndrome in the study. In other words, a total of 12723 acceleration data was measured for 5 different patients. ANN was trained using the data which are measured from H1 by both developed accelerometer (as XYZ input) and spirometer (as target/desired output).

All of the data measured from H1 were divided into two: Training Data: 605×3 and Test Data: 316×3 . Then training data were applied to ANN. After the network was trained, 316 test data were applied to the network. The resultant graphs showing ANN performance is given in Fig. 5. In this Fig. 5, it shows that apnea has occurred. ANN system, trained with H1 ACC data, can detect apnea events successfully for H1.

Then, the other 4 patients' data were applied to this network (trained by using only H1 data, and apnea events were detected. The calculated MSE of each one is tabulated in Table 1.

Performance of ANN for the patients H2, H3, H4, and H5 are given in Fig. 6 with Spirometer measurement result and accelerometer readout values. ANN system, trained with only H1 ACC data, can detect apnea events successfully for H2, H3, H4, and H5 as well as H1. This means that, after the successful learning step, the ANN system can monitor the apnea situation for any patients simultaneously.

The confusion matrix of the ANN for all the patients has been given in the Table 2.

Table 2
 The confusion matrix of the ANN for all the patients.

A	P	
	Predicted (NO)	Predicted (YES)
Actual (NO)	21444	38
Actual (YES)	30	1424

4. Conclusions and discussion

In this paper, a sleep apnea event detection system is presented by using ANN from directly acceleration values. Measurements are performed by MEMS-based accelerometer and Industrial Spirometer (Fukuda Sangyo brand spiroanalyz ST-75 model, Prg ver: 2.36B 16-Bit) simultaneously. Total of 12723 acceleration data is measured from 5 different patients.

In the designed ANN, three layers were formed that 3 neurons in the hidden layer, 2 neurons at the input and 2 neurons at the output layer. For the number of neurons in the hidden layer, 1-3-5-10-18-20-25 values were tried, and the network with 3 hidden neurons giving the most suitable result was selected. The best result in 7000 iterations was reached (the number of iterations was tried up to 10.000 with 1000 steps). 605 data of only H1 measurements are used to train ANN, and then all data used to check the performance of the ANN as well as H2, H3, H4, and H5 measurement result. MSE performance benchmark shows us that trained ANN successfully detects apnea event.

One of the contributions of this study to literature is that only ACC data are used in the ANN training step. After training for one patient, the ANN system can monitor the apnea event situation on-line for others.

Depend on lying position ACC measurement can be changed. As a next step, it is planned to find the relation between axis acceleration values and diaphragm movement related to lying position to detect apnea event. Besides that, in order to increase ANN performance as well as the accelerometer misaligning, one or more extra sensors can be added to the system.

Acknowledgments

This project was funded by the Deanship of Scientific Research (DSR), King Abdulaziz University, Jeddah, Saudi Arabia (The project number is 135-424-D1441). The authors, therefore, gratefully acknowledge DSR technical and financial support.

Ethical approval

The method of work and the developed measuring instrument were approved by the faculty member of Ondokuz Mayıs University, medical faculty, clinical research unit ethics committee with number 2015/123.

Author contributions

All the authors actively participated in the literature analysis, the interpretation of results and the preparation of the manuscript. All authors read and approved the final manuscript.

Conflicts of interest

The author declares that there is no conflict of interest regarding the publication of this paper.

References

- [1] Findik G, Aydoğdu K, Kaya S. Travma sonrası semptomatik hale gelen diyafram evantrasyonu. *Turkish J Thoracic Cardiovasc Surg* 2011;19(1):107–9.
- [2] Akyolcu N. Kanserli hastalarda dispne ve hemşirelik bakımı. *C.Ü. Hemşirelik Yüksekokulu Dergisi* 2002;6(1):1–8.
- [3] Berry RB, Budhiraja R, Gottlieb DJ, Gozal D, Iber C, Kapur VK. Rules for scoring respiratory events in sleep: update of the 2007 AASM manual for the scoring of sleep and associated events. *J Clin Sleep Med* 2012;8(5):597–619. <https://doi.org/10.5664/jcsnm.2172>.
- [4] Angius G, Raffo L. A sleep apnea keeper in a wearable device for continuous detection and screening during daily life. *Proc Comput Cardiol, Italy* 2008;35:433–6. <https://doi.org/10.1109/CIC.2008.4749071>.
- [5] Otero A, Dapena SF, Felix P, Presedo J. A low cost screening test for obstructive sleep apnea that can be performed at the patient's home. In: *Proceedings of 6th international symposium on intelligent signal. IEEE*; 2009. p. 199–204. <https://doi.org/10.1109/WISP.2009.5286533>.
- [6] Varady P, Micsik T, Benedek S, Benyo Z. A novel method for the detection of apnea and hypopnea events in respiration signals. *IEEE Trans Biomed Eng* 2002;49(9):936–42. <https://doi.org/10.1109/TBME.2002.802009>.
- [7] Xie B, Minn H. Real-time sleep apnea detection by classifier combination. *IEEE Trans Inf Technol Biomed* 2012;16(3):469–77. <https://doi.org/10.1109/TITB.2012.2188299>.
- [8] Bucklin CL, Das M, Luo SL. An inexpensive accelerometer-based sleep-apnea screening technique. In: *Proceedings of the IEEE National, Aerospace and Electronics Conference (NAECON)*. IEEE. p. 396–9. <https://doi.org/10.1109/NAECON.2010.5712984>.
- [9] Güven SF. Scoring of the respiratory recordings. *Polysomnography* 2013;15(2):30–4. <https://doi.org/10.5152/solunum.2013.032>.
- [10] Tagluk MA, Akin M, Sezgin N. Classification of sleep apnea by using wavelet transform and artificial neural networks. *Expert Syst Appl* 2010;37(2):1600–7. <https://doi.org/10.1016/j.eswa.2009.06.049>.
- [11] Karamanli H, Yalcinoz T, Yalcinoz MA, Yalcinoz T. A prediction model based on artificial neural networks for the diagnosis of obstructive sleep apnea. *Sleep Breathing* 2016;20:509. <https://doi.org/10.1007/s11325-015-1218-7>.
- [12] Kirby SD, Eng P, Danter W, George CF, Francovic T, Ruby RR, et al. Neural network prediction of obstructive sleep apnea from clinical criteria. *Chest* 1999;116(2):409–15.
- [13] Chen LF, Su CT, Chen KH, Wang PC. Particle swarm optimization for feature selection with application in obstructive sleep apnea diagnosis. *Neural Comput Appl* 2012;21:2087. <https://doi.org/10.1007/s00521-011-0632-4>.
- [14] Uçar MK, Bozkurt MR, Bilgin C, Polat K. Automatic detection of respiratory arrests in OSA patients using PPG and machine learning techniques. *Neural Comput Appl* 2017;28:2931. <https://doi.org/10.1007/s00521-016-2617-9>.
- [15] Suzuki T, Kameyama K, Inoko Y, Tamura T. Development of a sleep apnea event detection method using photoplethysmography. *Conf Proc IEEE Eng Med Biol Soc* 2010;2010:5258–61. <https://doi.org/10.1109/IEMBS.2010.5626291>.
- [16] Tripathy RK. Application of intrinsic band function technique for automated detection of sleep apnea using HRV and EDR signals. *Biocybernet Biomed Eng* 2018;38(1):136–44. <https://doi.org/10.1016/j.bbe.2017.11.003>.
- [17] Hassan AR, Haque MdA. Computer-aided obstructive sleep apnea screening from single-lead electrocardiogram using statistical and spectral features and bootstrap aggregating. *Biocybernet Biomed Eng* 2016;36(1):256–66. <https://doi.org/10.1016/j.bbe.2015.11.003>.
- [18] Falie D, Ichim M (2010) Sleep monitoring and sleep apnea event detection using a 3D camera. *Communications (COMM)*, 2010 8th International Conference on. IEEE, doi: 10.1109/ICCOMM.2010.5509015
- [19] Koley BL, Dey D. Real-Time adaptive apnea and hypopnea event detection methodology for portable sleep apnea monitoring devices. *IEEE Trans Biomed Eng*. IEEE 2013;60(12):3354–63. <https://doi.org/10.1109/TBME.2013.2282337>.
- [20] Selvaraj N, Narasimhan R. (2013). Detection of sleep apnea on a per-second basis using respiratory signals, 35th Annual International Conference of the IEEE. IEEE, 2124–2127.
- [21] Sümbül H, Yüzer AH. Detection of respiratory signals according to different positions using acceleration sensor, 23rd Signal Processing and Communications Applications Conference (SIU). IEEE Conf Publ 2015;1:279–82. <https://doi.org/10.1109/SIU.2015.7129837>.
- [22] Al-ashkar F, Mehra R, Mazzone PJ. Interpreting pulmonary function tests: Recognize the pattern, and the diagnosis will follow. *Cleve Clin J Med*. 2003;70(10):866–81.
- [23] Sümbül H, Yüzer AH. Measuring of Diaphragm Movements by using iMEMS Acceleration Sensor. In: *International Conference on Electrical and Electronics Engineering, ELECO2015, IEEE Conference Publications* 166–170. <https://doi.org/10.1109/ELECO.2015.7394532>.
- [24] Farre R, Montserrat JM, Navajas D. Noninvasive monitoring of respiratory mechanics during sleep. *Eur Respir J* 2004;24:1052–60. <https://doi.org/10.1183/09031936.04.00072304>.
- [25] Rumiński Jacek. Analysis of the parameters of respiration patterns extracted from thermal image sequences. *Biocybernet Biomed Eng* 2016;36(4):731–41. <https://doi.org/10.1016/j.bbe.2016.07.006>.
- [26] Quazi MH, Kahalekar SG. Artifacts removal from EEG signal: FLM optimization-based learning algorithm for neural network-enhanced adaptive filtering. *Biocybernet Biomed Eng* 2017;37(3):401–11. <https://doi.org/10.1016/j.bbe.2017.04.003>.
- [27] Morillo D, Rojas Ojeda JL, Crespo Foix LF, Jimenez A. An accelerometer-based device for sleep apnea screening. *IEEE Trans Inf Technol Biomed* 2010;14(2):491–9. <https://doi.org/10.1109/TITB.2009.2027231>.
- [28] Chang KM, Shin-Hong L. Wireless portable electrocardiogram and a tri-axis accelerometer implementation and application on sleep activity monitoring. *Telemedicine and e-Health* 2011;17(3):177–84. <https://doi.org/10.1089/tmj.2010.0078>.
- [29] Roetenberg D, Slycke PJ, Veltink PH. Ambulatory position and orientation tracking fusing magnetic and inertial sensing. *IEEE Trans Biomed Eng* 2007;54(5):883–90. <https://doi.org/10.1109/TBME.2006.889184>.
- [30] Sümbül H, Yüzer AH. 3D Monitoring of lying position for patients with positional sleep apnea syndrome. *J New Results Sci* 2016;12(2016):59–70.

- [31] Sumbul H, Yuzer AH. Development of diagnostic device for COPD: A MEMS Based Approach. *IJCSNS Int J Comput Sci Network Secur* 2017;17(7):196–203.
- [32] Rendon DB, Rojas Ojeda JL, Crespo Foix LF, Morillo DS, Fernandez MA. Mapping the human body for vibrations using an accelerometer. *Conf Proc IEEE Eng Med Biol Soc. IEEE* 2007:1671–4. <https://doi.org/10.1109/IEMBS.2007.4352629>.
- [33] Wu D, Wang L, Zhang YT, Huang BY, Wang B, Lin SJ, et al. A wearable respiration monitoring system based on digital respiratory inductive plethysmography 4844–7. *Conf Proc IEEE Eng Med Biol Soc* 2009. <https://doi.org/10.1109/IEMBS.2009.5332665>.
- [34] Reinvo T, Hannula M, Sorvoja H, Alasaarela E, Myllyla R. Measurement of respiratory rate with high-resolution accelerometer and EMFit pressure sensor. *Sensors Applications Symposium. IEEE* 2016:192–5. <https://doi.org/10.1109/SAS.2006.1634270>.
- [35] Phan DH, Bonnet S, Guillemaud R, Castelli E, Pham Thi NY. Estimation of respiratory waveform and heart rate using an accelerometer. *Conf Proc IEEE Eng Med Biol Soc., IEEE* 2008:4916–9. <https://doi.org/10.1109/IEMBS.2008.4650316>.
- [36] Uyku Bozukluğu (2020), <http://uykubozuklugu.uludag.edu.tr/ltrt014.htm>, (last accessed: January, 2020)
- [37] Wang Q, Jin Y, Wei L, Feng A. Design of novel fire rescue system based on wireless sensor network. *Sens Transducers* 2013;157(10):168–72. https://doi.org/10.1007/978-3-642-31869-6_35.
- [38] Saritas I, Ozkan IA, Sert IU. Prognosis of prostate cancer by artificial neural networks. *Expert Syst Appl* 2010;37(9):6646–50. <https://doi.org/10.1016/j.eswa.2010.03.056>.
- [39] Ozkan IA, Herdem S, Saritas I. FPGA-based self-organizing fuzzy controller for electromagnetic filter. *Neural Comput Appl* 2017;28(9):2535–43. <https://doi.org/10.1007/s00521-016-2199-6>.
- [40] Kennedy J, Eberhart RC. (1995). Particle swarm optimization. In *Proceedings of the IEEE international conference on neural networks. IEEE*, 4:1942–1948).
- [41] Denoeux T, Lengellé R. Initializing back propagation networks with prototypes. *Neural Networks* 1993;6(3):351–63. [https://doi.org/10.1016/0893-6080\(93\)90003-E](https://doi.org/10.1016/0893-6080(93)90003-E).
- [42] Shamsuddin SM, Ibrahim AO, Ramadhena C. (2013).. Weight Changes for Learning Mechanisms in Two-Term Back-Propagation Network, *Artificial Neural Networks - Architectures and Applications*, Prof. Kenji Suzuki (Ed.), InTech, DOI: 10.5772/51776.